



SPX-FLEX

Swing Pipe

APPLICATIONS

The flexible swing joint absorbs impacts and any pressure caused by cars or turf maintenance equipment.

FEATURES

- Simplicity : Unique material offers excellent pipe flexibility and greater kink resistance for fast, efficient installation.
- Reliability : The barbed fittings resistance to handling is significantly greater than that of other flexible swing pipe.
- Durability : SPX-FLEX swing pipe are designed to withstand high pressure and pressure spikes. Their easy installation ensures the most reliable connection every time.

- Available in several coil lengths : 30 m, 50 m or 100 m.
- Linear, low density polyethylene material.
- New, kink-resistant, ultra-flexible version.
- Colour : Black with green stripes for easier identification.
- Special packaging : Coil is easier to unroll.

SPECIFICATIONS

Nominal inside diameter : 12.5 mm
 Minimum wall thickness: 2.5 mm
 Maximum operating pressure and temperature: 5.5 bar and 43°C.

MODELS

SPX-FLEX: 30 m roll
 SPX FLEX: 50 m roll
 SPX FLEX: 100 m roll



SP-100

Swing Pipe

APPLICATIONS

Used in conjunction with SB Barb Fittings as a flexible swing joint assembly to protect underground sprinklers by absorbing impact caused by cars or turf maintenance equipment.

FEATURES

- Linear low-density polyethylene material resists breaks
- Reduces the number of fittings on mainline by allowing easy installation of sprinklers in the corners.
- Easy-to-install: change the height and lateral position of a spray/rotor without modifying the installation.

- Allows fast connection. Important: do not use any lubricant (grease, soap, oil, etc.)

SPECIFICATIONS

Inside diameter: 12.5 mm
 Operating water pressure rating: up to 5.5 bar

MODEL

SP-100/30 (30m coil)



SWING ASSEMBLY

Swing Pipe and Fittings Kit For sprinkler installation

APPLICATIONS

The flexible swing joint absorbs impacts and any pressure caused by cars or turf maintenance equipment.

FEATURES

- 30 cm Swing Pipe kit with 2 elbow fittings for fast installation.
- Kink-resistant, low density, linear polyethylene
- Reduces the number of fittings on the mainline by facilitating installation of sprinklers in corners.
- Easy to install. The height and lateral position of a spray head/rotor can be adjusted without modifying the installation.
- Fast connection. Important: Do not use any lubricant (grease, soap, oil, etc.)

SPECIFICATIONS

Nominal inside diameter : 12.5 mm
 Minimum wall thickness: 2.5 mm
 Maximum operating pressure and temperature: 5.5 bar and 43°C.

Mounted with 2 male elbow fittings - 1/2" (15/21) or 3/4" (20X27).

Maximum operating pressure : 5.5 bar

MODELS

LSBE050K: SP100 - 30 cm + 2 SBE-050
 LSBE075K: SP100 - 30 cm + 2 SBE-075



Example of mounting

